



MST01

Industrial Temperature
and Humidity Sensor

Datasheet



PRODUCT OVERVIEW

MST01 is an industrial temperature and humidity Bluetooth® sensor developed by Minew for professional use. It is designed for environmental monitoring in manufacturing, healthcare, warehousing, etc. Probes are dust and stain-proof and come in different styles. The body is designed to suit all weather conditions and all industrial scenarios. Multiple temperature and humidity thresholds can be set. When values are exceeded, alarms will be triggered, and the screen will be prompted, in order for administrators to react. MST01 can store substantial data locally to mitigate data loss.



KEY FEATURES



Temperature and humidity threshold alarms



Multiple probe options
real-time data display



Large range
high precision



200 meters of
broadcast distance



20,480 local
data storage



IP65 dust &
water resistance

APPLICATION SCENARIOS



Smart Healthcare

The storing environment of pharmaceuticals is controlled precisely. Drugs and vaccines should be monitored under strict temperature and humidity standards automatically 24 hours a day in transportation or in storage. MST01 can calculate the mean kinetic temperature, MKT, while storing a large amount of data locally. It supports threshold alarm, strong anti-interference, and timely feedback.



Smart Warehousing

MST01 supports a variety of probes, with a large measurement range and high precision. It is suitable for warehouses, wine cellars, cold storage, and other warehouse scenarios that often require precise monitoring of ambient temperature and humidity to keep fresh produce under ideal conditions. MST01 data can be displayed in real time for easy viewing, simplifying inspection, and improving efficiency.

* **Note:** Application cases above are only as a reference, more applications realized are based on users' software algorithm ability.

PRODUCT SPECIFICATIONS

BASIC SPECIFICATIONS

Product image



Model	MST01-01	MST01-02	MST01-03	MST01-04
Material	ABS + PC	ABS + PC	ABS + PC	ABS + PC
Color	White	White	White	White
Size Main body (L * W * H)	75 * 66.5 * 27 mm (without bracket) 82 * 66.5 * 31.3 mm (with bracket)			
Size Probe (D*H)	Φ15.5 * 48 mm	Φ15 * 30.5 mm	1 m (probe + cable length)	1 m (probe + cable length)
Weight	106.8 g	103.1 g	131.1 g	128.9 g
Protection	IP65	IP64	Main body IP65 Probe IP67	Main body IP65 Probe IP67
Battery	1 lithium battery(replaceable)			
Battery capacity	2700 mAh			
Battery life	3 years (default configuration, normal temperature environment)			
Sensor	Temperature and humidity sensor			
Button	2			
LED	1 red light, 1 blue light			
NFC	None			
Buzzer	Supported			
OTA	Supported			
Configure APP	MSensor ^[1]			

* [1] Bluetooth-related SDK is available, please contact our sales team for details.

TECHNICAL SPECIFICATIONS

Chip	nRF52 Series
Bluetooth version	Bluetooth® LE 5.0
Broadcast power	-40 dBm ~ +4 dBm
Broadcast distance	Up to 200 meters (open environment)
Security	Supports changing passwords, anti-malicious connection

ACCURACY PARAMETER				
Product image				
Model	MST01-01	MST01-02	MST01-03	MST01-04
Measure temperature	-30℃ ~ 70℃	-30℃ ~ 70℃	-30 ~ 80℃	-40 ~ 125℃
Measure humidity	0 ~ 100% RH	0 ~ 100% RH	0 ~ 100% RH	0 ~ 100% RH
Temperature accuracy	±0.3℃ (-10~30℃) ±0.5℃ (other ranges)	±0.3℃ (-10~30℃) ±0.5℃ (other ranges)	±0.3℃ (-10~30℃) ±0.5℃ (other ranges)	±0.5℃ (-30 ~ 80℃) ±1℃ (other ranges)
Humidity accuracy	±3% RH (10% ~ 95% RH, 20℃)			
Temperature resolution	0.01℃			
Humidity resolution	0.01% RH			
Operating temperature	-30 ~ 70℃			
Working humidity	0 ~ 95% RH, no condensation			
Features	Fast response speed	PE cotton protective cover, dustproof and anti-condensation, good stability	PE cotton protective cover, dustproof and anti-condensation	High sensitivity, fast response, high temperature resistance

COMPATIBILITIES

SUPPORTED SYSTEMS	SUPPORTED MODELS
iOS 10.0 and above	iPhone6 /6 Plus /6S/ 6S Plus /7 /7 Plus /8 /8 Plus / x /xr /xs /xs max / SE /SE2 /11 /11 pro /11 pro max
Android 4.3 and above	Samsung, Xiaomi, Huawei, Honor, OnePlus, Google pixel, etc.

BASIC OPERATION

Power on: The product is turned off by default when shipped. Hold the power button  for 3 seconds, when the blue light stays on for 3 seconds, it means that it has been powered on and the display screen displays the detection data.

Power off: When on, turn it off on MSensor App, and no data is displayed on the display.

Toggle: Pressing the function button  the screen will display in rotation: current temperature, current humidity, average temperature, average humidity, MKT temperature, upper temperature U1, upper temperature U2, lower temperature L1, lower temperature L2, upper humidity U1 and lower humidity L1.

Mark: Hold the function button  in the current temperature and humidity interface for 3 s, you can mark the current temperature and humidity, and the screen will show a "MARK" label.

Battery: When the battery is low, the red light flashes every 10 s.

Threshold alarm: the red-light flashes 2 times per second, the buzzer rings 2 times per second, and the alarm stops after 30 seconds of alarm or when the temperature and humidity return to the warning value; click the switch button to stop the alarm when it alarms.

APP connection and disconnection: When the product is successfully connected or disconnected from the App, the blue light flashes 2 times.

OTA upgrade: The blue light is always on during the OTA upgrade, and the blue light goes out after the upgrade.

INSTALLATIONS

Double-sided tapes

Surfaces: Ceramic, glass/epoxy, acrylic, PBT, ABS, PC, rigid PVC, and others. It is not recommended to use the default double-sided tape on walls (such as cement, gypsum board, etc.) with gray texture, incomplete drying, aging, moisture, etc., or there is a risk of peeling off. You can choose 3M double-sided foam tape or nail free glue as alternatives.

Requirements: No dust on the material surface and clean it before installation. Before pasting, increase the viscosity of the double-sided paste with a hairdryer firstly, and then press for seconds sequentially and stick over half-hours; or leave the device over 72 hours after pasting for better stability.

Bracket screw installation

The product can be shipped with a bracket, which supports the wall, ceiling, and corner, and can be secured with screws.

Surfaces: The screw should be installed on a solid surface, such as a wall, where it is not easy to loosen.

Steps:

- ① Drill screw holes on the surface to be installed.
- ② Insert the green expansion plug into the surface hole.
- ③ Put the MST01 into the mounting bracket.
- ④ Twist screws onto the expansion plug so that the product can be installed firmly.

Please contact our sales team if you have any questions about the installation environment.

PRECAUTIONS

- This product should be installed in a place where the temperature is relatively stable and can best represent the measured ambient temperature and humidity.
- Please avoid installation in areas with drastic changes in temperature, strong airflow, or almost no airflow. Do not use in a salt spray environment or corrosive gas environment.
- When using the product, it is recommended to use a low-grade broadcast power and a longer broadcast period to extend the service life of the product.
- The product is only splash-proof and does not support underwater work.
- Do not use the product beyond the designed working temperature of the product to avoid damage. It is recommended to store the product under house temperature (0℃ ~ 40℃) when not in use.
- Avoid being exposed to direct sunlight for a long time to avoid the aging of the shell.
- Please do not disassemble the main shell without permission, our company will not be responsible for any damage caused.
- If you have any other questions, please contact our sales team or technical support team.

CERTIFICATIONS

CE FCC RoHS SRRC

* Note: CE, FCC, RoHS, SRRC numbers are available , if you need other certifications, please contact our business team .

PACKAGING INFORMATION

Inner carton

Pictures



Name	MST01-01	MST01-02	MST01-03	MST01-04
Quantity	18	16	4	4
Individual product + accessories net weight	106.8g+3.9g	103.1g+3.9g	131.1g+3.9g	128.9g+3.9g
Gross weight	2200g	1884g	640g	625g
Sizes	38.5x22x10.2cm	30.5x22x9.5cm	30.6x11x9.5cm	30.6x11x9.5cm

Outer box

Pictures



Name	MST01-01	MST01-02	MST01-03	MST01-04
Quantity	54	64	32	32
Gross weight	7050g	7970g	5526g	5431g
Sizes	32x23.5x40cm	32x23.5x40cm	32x23.5x40cm	32x23.5x40cm

QUALITY ASSURANCE

The factory has already obtained the certification of ISO9001 Quality System. Each product has been strictly tested (tests include transmission power, sensitivity, power consumption, stability, aging, etc.).

Warranty Period: 12 months from the date of shipping (Battery and other accessories excluded).

DECLARATION

Statement of Rights:

The contents of this manual belong to the Manufacturer of Minew Technologies Co., LTD, Shenzhen, and are protected by Chinese laws and applicable international conventions related to copyright laws. The contents can be revised by the company according to the technological development without prior notice. Anyone, companies, or organizations cannot modify the contents and cite the contents of this manual without Minew's permission, otherwise, Violators will be held accountable according to law.

Disclaimer:

Minew team reserves the right to the final explanation of the document and product differences. The Minew group is not responsible for liability of property or personal injury with the wrong operation if users develop related products without checking the technical specifications of this manual.



SHENZHEN MINEW TECHNOLOGIES CO., LTD.



www.minew.com



info@minew.com



www.minewstore.com